

MARKED UP COPY OF SPECIFICATION

DIEDERICHS: W1.2259 PCT-US

[Specification]

Optical System for Forming [Creating] an Illuminated Pattern [Structure]

CROSS-REFERENCE TO RELATED APPLICATIONS

[001] This patent application is the U.S. national phase, under 35 U.S.C. 371, of PCT/EP 2005/051161, filed March 15, 2005; published as WO 2005/092619 A1 on March 23, 2004, and claiming priority to DE 10 2004 04 532.6, filed March 23, 2004, the disclosures of which are expressly incorporated herein by reference.

FIELD OF THE INVENTION

[002] The present invention is directed [relates] to an optical system for forming [creating] an illuminated pattern [in accordance with the preamble of claim 1]. The illumination pattern is formed on a surface of a material that is moving relative to the formed pattern. An illumination arrangement, with several pulsed light sources, is operated by a control device and emits light for generating the pattern.

BACKGROUND OF THE INVENTION

[003] Optical systems for forming an illuminated structure are [The application is] used primarily in connection with the recording of images of machine-processed material in the field of industrial image processing, such as, for example, in the recording of imprinted material which is processed in connection with stocks and bonds. The [, wherein the] optical system is used in or on a printing press, preferably in or on a rotary printing press, and in particular in or on a printing press operated

in, for example, [by means of] an offset printing method, a steel engraving method, a screen printing method or a hot-process embossing method. Alternatively, or in addition [additionally] to such an [the] arrangement in or on a printing press, an [the] optical system can also be arranged in or on a machine which further processes a printed product. Image recording is performed for the purpose of providing an at least partial, and preferably complete image representation of the moving imprinted material. This image representation can be done [,] with or without taking a measurement of previously determined characteristics of the imprinted [this] material, in order to evaluate this material regarding the quality of a process step previously performed in the machine. Optical systems of this general type are typically employed, for example, in an inline inspection system and therefore are typically a component of such an inline inspection system.

[004] An image reading device is known from DE 35 27 300 C2. An [, wherein an] illumination arrangement, with several groups of light sources, is provided. The [, wherein the] groups of light sources emit light for use in generating an illuminated strip. A [, wherein a] control arrangement operates the groups of light sources in a pulsed manner. Photo [, wherein photo]-sensors, which are arranged in rows, detect light which is reflected from the surface of the material. The [, wherein the] photo- sensors constitute a line-scanning camera. An [, wherein an] electrical current source, that is controlled by the control arrangement, is assigned to the groups of light sources. A [, wherein a] length of time, in which the light sources are switched-on, is synchronized with a length of the line-scanning camera exposure time.

[005] A method for checking web-shaped transparent material, and in particular, for checking a paper web, which is suitable for application in the print industry, is known from DE 41 02 122 A1.

Flash bulbs, which are [, wherein flashbulbs] constructed from light-emitting diodes or from laser diodes, radiate through a paper web. Light, which is [, so that light] being radiated through the paper web, impinges on a CCD matrix of a camera to generate [for generating] a video signal. Light [, wherein light] leaving the illumination arrangement, in the direction of the paper web, radiates through a frosted diffusor disk.

[006] A printing press with an inline image inspection system, for use in the inspection of a printed product produced in the printing press, is known from DE 43 21 177 A1. An [, wherein an] image detection arrangement is provided, which delivers image data of the printed product to a computing device. The [, wherein the] image detection arrangement consists of a measuring module, or of several measuring modules, each of which scans a defined image area of the printed product, and of at least one associated receiving device. The receiving device [, which] makes the image data available in an electric form and [which] is preferably spatially separated from the measuring modules. The [, wherein the] measuring modules and the at least one receiving device are connected with each other by at least one image conductor. An [, wherein an] illumination arrangement, consisting of precision halogen lamps, is assigned to the image detection device. A [wherein, when charged with blowing air, a] blow pipe, with openings in the direction of the printed product, when charged with compressed air maintains the printed product at a defined distance from the illumination arrangement and simultaneously cools the illumination arrangement by use [means] of the blowing air.

[007] An illumination arrangement for an optical inspection system, for use in the inspection of surfaces, is known from DE 100 61 070 A1. Several [, wherein several] support panels, which are

preferably of the same length and are electrically connected with each other, and each of which is provided with several rows of light-emitting diodes, have been inserted in a line-shaped manner into a common rigid, profiled mounting device. The mounting device [, which] can be cut in length to correspond to an object surface which is to be scanned by the use [means] of constant light radiation. A [, wherein a] thermal connection between the support panels and the profiled mounting device, for cooling the light-emitting diodes and their electronic control device, is provided by [means of] a mechanical connection.

[008] A device for the quality control of printed matter is known from DE 202 13 431 U1. This device [, which also] constitutes an inline image inspection system which is arranged in a printing press. An [, wherein an] illumination arrangement, configured [designed] as a fluorescent tube, and an image recording device, configured [designed] as a line-scanning camera, are employed.

[009] An inline image inspection system for a printing press, and in particular for a sheet-fed offset printing press, is known from DE 203 03 574 U1. An [, wherein an] illumination arrangement that is configured [designed] as a fluorescent tube, is arranged underneath a foot pedal and close to a counter-pressure cylinder which is conveying an imprinted material. An [, and an] image recording device, which is provided [designed] as a line-scanning camera, is arranged at a comparatively greater distance from the counter- pressure cylinder in association with the last printing group of the printing press.

[0010] A device for a line-shaped illumination of sheet material, such as banknotes and securities, is known from EP 0 762 174 A2. A [, wherein a] cylindrical mirror with two mirror segments is provided. The [, wherein the] mirror segments form an elliptical base surface having two focal

lines. The [, wherein the] width of the mirror segments has been selected to be larger than or equal to the width of the sheet material. The [, wherein the] sheet material [metal], which is transported in the transport direction perpendicularly to the first focal line, is arranged in this first focal line. A [, and a] cold light source, such as, for example a row of light-emitting diodes (LEDs), is arranged in the second focal line. A [, wherein a] detector, such as, for example a CCD array, or photodiodes, which can be arranged individually or in groups, detects the light reflected by the sheet material and converts it into signals for processing in a processing installation.

[0011] An inspection system is known from USP 4,972,093. A [, wherein a] moving test object is subjected to a strobe of light lasting between 20 ms and 200 ms from a light-emitting diode arrangement which is controlled in a pulse-like manner. An [, and an] area-scanning camera takes a picture of the entire test object.

[0012] An optical system for forming [creating] an illuminated pattern on a surface of a material which is moved relative to the pattern is known from USP 5,936, 353. An [, wherein an] illumination arrangement with several light sources, which are switched in series, emits light for forming [creating] the pattern. A [, wherein a] detection device, with at least one detector, detects light reflected from the surface of the material. The [, wherein the] light sources are arranged on a panel which [, wherein the panel] is arranged on a support. That [, wherein the] support has at least one conduit in its interior. A [, wherein a] liquid or gaseous cooling medium, for use in cooling the light sources, flows through the conduit.

[0013] A device for use in the control of light-emitting diodes with a constant current source, which form a line-shaped illumination arrangement, is known from JP 1-255 371 A. A [, wherein

a) driving circuit of the light-emitting diodes is connected with a line- scanning camera via a scanning control circuit and a multiplexer. The [, so that] light-emitting diodes of the illumination arrangement, which are in operative connection with each other, and photo- sensors of the line- scanning camera are synchronized with each other.

FIELD OF THE INVENTION

[0014] The object of the present invention is directed to [based] on providing an optical system for use in forming [creating] an illuminated pattern. A [, wherein a] picture is taken with the same amount of light over a wide range of the speed of the moving material.

[0015] In accordance with the present invention, this object is attained by the provision of an optical system for use in generating an illuminated pattern on a surface of a material which is moving relative to the pattern. An illumination arrangement, which has several light sources that are operated in a pulsed manner by a control device, emits the light which generates the pattern. A detection device detects the light emitted by the light sources. A switched-on time of the light source is controlled by the control device and is synchronized with a length of an exposure time of the detection device. The length of the switched-on time of the light source is arranged within the exposure time of the detection device. [means of the characteristics of claim 1.]

[0016] The advantages to be gained by [means of] the present invention consist, in particular, in that the surface of the moving material is always illuminated with the same amount of light, regardless of the speed of the moving material. Accordingly, [, because of which] a constant brightness results for image recording[,] and unusable image recordings are avoided. Additionally [Also], the length of time that the light source is switched on always constitutes a partial amount of

the length of the exposure time of the line-scanning camera. A [, so that a] fixed correlation between the length of time that the light source is switched on, and the length of the exposure time of the line- scanning camera is always assured for the timing. A [As a rule, a] digital line-scanning camera typically has an electronic shutter which, at the end of a selected [the] exposure time of the line-scanning camera, puts out a read-out pulse for use in reading out the electrical charge which was collected by the detectors as a result of the light reflected from the surface of the moving material. Overflowing [So-called overflowing] of the detectors of the line-scanning cameras, which are sensitive to electrical charges, is avoided by the use [means] of the correlation, in accordance with the present invention, between the time the light source is switched on and the exposure time of the line-scanning camera. In [Instead, in] an advantageous manner, a barrier results over a wide range of the speed of the moving material and therefore provides an unequivocal separation between sequential detectors, which are successively arranged in the movement direction of the line-scanning camera.

[0017] A further advantage of the optical system in accordance with the present invention lies in that the material, on whose surface the pattern is to be created, need not be arranged in a focal point, which is located in a direct or in a redirected beam path of the light being emitted by the light source, in order to make the pattern appear with a sufficiently strong illumination. An arrangement of the pattern, relative to the optical system, which is independent of the focal point, is advantageous. In [, because in] that case, it is possible to do without an exact dimensional accuracy with respect to [regarding] the distance between the pattern and the illumination arrangement. The distance of the proposed optical system is therefore tolerant with respect [in

regard] to the illuminated material. Moreover, a sufficient distance is provided between components of the optical system, whose functioning [function] could be impaired by soiling, such as, for example, by dust or by rubbed-off particles, and the material. In [, in] particular, [also] in regard to a transport device which moves the material, this sufficient distance [which], under the existing operating conditions in a printing press, keeps the optical system and the material out of direct contact. This sufficient distance also [, and] preferably arranges the optical system outside the range of [the] particles of dirt which may be stirred up by the moving material.

[0018] An illuminated strip, which is illuminated by the illumination arrangement and which is of a width that extends [which] orthogonally [extends] on the surface of the material, with [in] respect to its length, i.e. a two-dimensional flat pattern, has an [the] advantage over a line-shaped, or an [i.e.] only one-dimensional illuminated pattern, which is focused on a focal point. The [, that the] illuminated pattern dependably appears to a detection device as a virtual, line-shaped illumination arrangement [to a detection device] for detecting the light reflected by the surface of the material. That material [, which] is arranged at [under] a reflective angle with [in] respect to a surface of the material, which is reflective at least in part, even if the surface of the material is configured [designed] to be in a relief shape. It [, because it] is assured, based on the width of the illuminated strip, that a cross-sectional surface of a detection angle of the detection device, which exists on the surface of the material and within which the detection device is capable of detecting reflected light, will detect at least a portion of a cross-sectional surface of the light beam emitted by the illumination arrangement which extends over the width of the illuminated strip. There is the danger, in connection with a device which illuminates the material only in a line-like manner,

that the focused light beams may be [are] reflected by a relief-like surface of the material outside of the detection angle of the detection device, so that, as a result, the focused light beam [it] cannot be detected. In contrast thereto, the [proposed] optical system in accordance with the present invention is also well suited for taking pictures of material with a diffusely reflecting surface. A shading effect very rarely [hardly] occurs, even with a material having [with] a relief-like surface.

[0019] The illumination arrangement of the [proposed] optical system of the present invention is preferably constructed by the use [means] of modules, such as, for example [i.e.] in independent functional units. This construction [, which] has the advantage that the length of a line of the line-shaped illumination arrangement can be adapted, without an expensive special production, by the use [means] of a simple alignment of prefabricated, preferably functionally identical modules, in the required amounts, to the width of the material to be illuminated, or at least to the width of the illuminated strip. It is possible, in the same way, to activate the light sources, in a selective positive manner, only in those modules which are required for illuminating the width of the material to be illuminated, or for illuminating at least the length of the illuminated strip. Such an activation [, which] has advantages [regarding] with respect to the efficiency of the construction and the operation of the optical system.

[0020] The employment of a plurality of light sources for each [per] module has the advantage that differences in the light emitted by the light sources, which differences are unavoidable in actual use, and which differences may exist in, for example, its wavelength, are compensated for by mixing the light beams of adjoining light sources. In this way, [, and that] the optical properties of the light emitted, as a whole, by the illumination arrangement are homogenized. Preferably, if [If

preferably] several groups of light sources are arranged in each module, and wherein the light sources that are assigned to the groups differ in their optical properties, such as, for example in the color of the light emitted by the light sources of each group, the individual groups of light sources can be selected in accordance with their application, such as, for example, by color, and can be controlled.

[0021] The [proposed] optical system in accordance with the present invention has the advantage that it charges an illuminated strip which possibly has a considerable length, of, for example, more than a meter, with a homogeneous, sufficiently large illumination strength, by the use [means] of an even light distribution in accordance with the requirements. The optical system [, and] can be adapted, in a simple way, to the respective requirements in connection with a printing press because [by means] of its modular construction, which is not very susceptible to interference. The [Since the] material to be illuminated need not be arranged in a focal point of the illumination arrangement. Accordingly , the requirement for an exact alignment of the vertical distance of the light sources with [in] respect to the surface of the material, as well as the monitoring of this distance during the running employment of the optical system, can also be omitted. This [, which] considerably simplifies the manipulation of the optical system at the site in an industrial installation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] Preferred [Exemplary] embodiments of the present invention are represented in the drawings and will be explained in greater detail in what follows.

[0023] Shown are in:

[0024] Fig. 1, a schematic top plan view a surface of a moving material with an illuminated strip
[in a view from above], in

[0025] Fig. 2, a schematic representation of the optical system in accordance with the present invention, in

[0026] Fig. 3, an individual light source of the illumination arrangement, in

[0027] Fig. 4, a line-like arrangement of light sources on a common board, in

[0028] Fig. 5, a light beam concentration by the use [means] of a first mirror, in

[0029] Fig. 6, a light beam concentration by the use [means] of a first mirror, along the length of
the illuminated strip, in

[0030] Fig. 7, a redirection of the light beam out of a central area of the light source by the use
[means] of a second mirror, in

[0031] Fig. 8, a redirection of the light beam out of a central area of the light source by the use
[means] of a second mirror, and wherein the beam is more tightly focused along the length of the
illuminated strip than along its width, in

[0032] Fig. 9, a schematic depiction of a focusing of the beam from a central area of the light
source by the use [means] of a convex lens, in

[0033] Fig. 10, a schematic depiction of a focusing of the beam from a central area of the light
source by the use [means] of a convex lens, wherein the beam is more tightly focused along the
length of the illuminated strip than along its width, in

[0034] Fig. 11, a schematic depiction of an at least partial superimposition of the beams from two
adjoining light sources with a scattering body placed in front, in

[0035] Fig. 12, a side elevation[lateral] view of the optical system, in

[0036] Fig. 13, a schematic depiction of a board equipped with light sources on a support through which a cooling medium flows, in

[0037] Fig. 14, a schematic depiction of a support through which cooling medium flows in two opposite directions, in

[0038] Fig. 15, a schematic depiction of a support with a cooling device with two Peltier elements, in

[0039] Fig. 16, a representation of the chronological behavior of the line-scanning camera and of that of the light sources, and in

[0040] Fig. 17, a perspective plan view of a reflector module in accordance with the present invention [a perspective plan view].

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0041] A material 03 with a surface 02, as represented in Fig. 1, is moved in a movement direction 04, indicated by an arrow, in a printing press, and in particular in a printing press which operating by the use [means] of an offset printing process. The movement takes place by use [means] of a transport device, which is not specifically represented [here], and which arranged in or on the printing press. The [, wherein the] movement of the material 03, in the course of the operation of the optical system, which operation will be described in greater detail in what follows, preferably occurs in only one movement direction 04, and this movement directed 04 is preferably linearly. The speed of the moving material can be constant, or can also be variable.

[0042] Preferably, the material 03 is embodied with a level surface and is flat, and is provided, for

example, as a sheet 03 or as a web 03 of material. In particular, the material 03 is embodied as an imprinted material 03, consisting of for example, [consisting of] paper and, particularly [for example], in the form of securities 03 or as a banknote 03. The surface 02 of the material 03 can have a relief shape or can have other structure irregularities protruding from the surface 02, or from a structure which is embossed into the surface 02 in the form of a depression. The [, wherein the] height or the depth of the relief or of the structure is very little in comparison with a width B03 of the material 03. At least a portion of the surface 02 of the material 03 is embodied to be reflective [reflecting], such as, for example, by the application of a reflective material, for example a lacquer, or a foil, through [by] the introduction of a window thread or another [other], preferably metallic substance into the material 03.

[0043] An illumination arrangement 06, which is only schematically [symbolically] represented in Fig. 2, forms [creates] an illuminated pattern 01, preferably in the form of an illuminated strip 01 of a length L01 and a width B01, as seen in [(Fig. 1)], wherein the width B01 of the illuminated strip 01 extends on the surface 02 of the material 03 orthogonally in relation to the length L01 of the illuminated strip. Preferably, the width B01 of the illuminated strip 01 is oriented in, or extends in, the movement direction 04 of the material 03, while the length L01 of the illuminated strip 01 is preferably oriented parallel with the width B03 of the material 03. Length L01 [and] can extend over portions of the width B03 of the material 03 or over its entire width B03. For example, the width B01 of the illuminated strip 01 is at least 3 mm, preferably is at least 8 mm. Therefore, the movement direction 04 of the material 03 is directed at least substantially parallel with [in] respect to the width B01 of the illuminated strip 01. The [, wherein the] movement

direction 04 of the material 03 lies within the plane defined by the length L01 and the width B01 of the illuminating strip 01. Preferably, the material 03 does not bulge, at least in the area of the illuminated strip 01.

[0044] Referring again to Fig. 2, the [The] illumination arrangement 06 has a plurality of light sources 07 which are arranged side-by-side in a line-shaped or linear manner, so that the entire illumination arrangement 06 is embodied to be line- shaped or linear. The light sources 07 of the illumination arrangement 06, arranged in a line-shaped or linear manner, are preferably arranged parallel with [in] respect to the length L01 of the illuminated strip 01. The light sources 07 have a respective distance A07 from the surface 02 of the material 03. That [, wherein the] distance A07 preferably lies between 30 mm and 200 mm, and in particular lies between 70 mm and 140 mm. Preferably, the distance A07 respectively extends perpendicularly with [in] respect to the surface 02 of the material 03. All of the light sources 07 of the illumination arrangement 06 are preferably identically configured [designed], such as, for example, as bright, high-intensity light- emitting diodes 07, or as laser diodes 07. It is also possible to provide separate groups of several light sources 07, each being respectively arranged in a line-shape or linear array, side-by-side, in the illumination arrangement 06. The [, wherein the] individual groups of light sources 07 differ in their optical properties, such as, for example in the wavelength, of the light emitted by each of them. For example, one group of light sources 07 can emit white light, while another group of light sources 07 can emit [emits] monochrome light. A [It can be provided that a] control device 23, which is preferably connected with the illumination arrangement 06, selects the groups of light sources 07 in accordance with the color of the light of the light sources 07 as a function of their

application, such as, for example, as a function of the nature of the surface 02 of the material 03, and controls them individually. In this way, the control device 23 can also control one [a] group of the several groups of light sources 07 independently of at least one other group of light sources 07 with respect [in regard] to their brightness and/or length of illumination. The illuminated strip 01 is arranged outside of the focal point located in the direct or redirected beam path of the light emitted by the light sources 07.

[0045] The illumination arrangement 06 can consist[s] of, for example, [of] several modules M61 to M65, as seen in [(Fig. 12)], which modules M61 to M65 are aligned side-by-side in a line, with each module M61 to M65 having several light sources 07 arranged in a line next to each other. A [, wherein a] partition 26 is arranged between two each adjoining modules M61 to M65 and is preferably arranged obliquely with respect [in relation] to the length L01 of the illuminated strip 01. The individual modules M61 to M65 of the illumination arrangement 06 can each be configured [designed] to perform identical functions, for example. In this way, it is possible, for example, to activate a line length of the illumination arrangement 06, which is comprised [composed] of the several side-by-side arranged modules M61 to M65, which activated line length corresponds to the width B03 of the material 03 to be illuminated, by switching on the light sources 07, which are arranged in a line, of the modules M61 to M65 involved. Alternatively, [, or it] is possible to activate a line length which corresponds [corresponding] to the length L01 of the illuminated strip 01 that is composed of several side-by-side arranged modules M61 to M65 by switching on the light sources 07, which are arranged in a line, of the modules M61 to M65 involved. It is also possible to activate the light sources 07 of individually selected modules M61

to M65 independently of the light sources 07 of other ones of the various modules M61 to M65.

[0046] [In an only two-dimensional representation,] Fig. 3 shows, in a representation which is only two-dimensional, an individual light source 07 of the illumination arrangement 06. The individual light source 07 emits its light at a solid angle ω [omega], wherein the solid angle ω [omega] covers an area AK which is cut out of a sphere, in other words an area of [i.e.] a surface AK of the sphere, up to the size of a hemisphere.

[0047] Fig. 4 depicts [shows] several, such as, for example, four, of the individual light sources 07 of the type represented in Fig. 3, which several light sources 07 are arranged next to each other in a line on a common board 21. An [The] electrical current source 22, which is assigned to the respective light sources 07, is preferably also arranged on the same board 21. The electrical current source 22 is preferably configured [designed] as a constant electrical current source 22, and in particular as a controllable constant electrical current source 22.

[0048] An [A part of an] optical system[, which] is preferably [is] a component of an inspection system that is arranged on, or in a printing press or a machine which further processes a printed product[, and [which] is used for assessing the quality of a printed product that is produced by [means of] the printing press. Such an optical system includes , besides the illumination arrangement 06, such as can be taken from Fig. 2, also[is] at least one detection device 08 with at least one detector 09, which at least one detector 09 is arranged at a distance A09 from the surface of the material 03. The [, wherein the] detector 09 detects light reflected by the surface 02 of the material 03. The detection device 08 is configured [designed], for example, as a camera 08, preferably as a line-scanning camera 08, and in particular as a line-scanning color camera 08. The

detection device 08 also preferably has a plurality of the detectors 09 arranged side- by-side in a line next to each other. The [, wherein the] detectors 09 which are arranged in a line, preferably are arranged parallel with [in] respect to the length L01 of the illuminated strip 01 and/or parallel with [in] respect to the width B03 of the material 03. A distance between lines of detectors 09, arranged in lines, preferably extends in the same direction as the movement direction 04 of the material 03. In other words, [, i.e.] lines of the detector 09, which are arranged following each other in the movement direction 04 of the material 03, are preferably arranged orthogonally with [in] respect to the movement direction 04 of the material 03. A [The] detector 09 of the detection device 08 can be embodied for example [be embodied] as a CCD array 09 or as a group of photodiodes 09. The detector 09 of the detection device 08 converts [the] detected reflected light into an electrical signal and supplies the electrical signal [for being evaluated] to an image processing device 24, for evaluation which image processing device 24 is connected with the detection device 08.

[0049] Fig. 5 shows that in the optical system in accordance with the present invention, at least one first mirror 11, with an effective surface 12 which is oriented along the length L01 and/or the width B01 of the illuminated strip 01, is assigned to the light sources 07. The [, wherein the] effective surface 12 of the first mirror 11 restricts the light emitted in the solid angle ω [omega] by at least one of the light sources 07 of the illuminating arrangement 06, to a [smaller] first envelope surface AH1 which is smaller than the spherical surface AK which is part of the solid angle ω [omega]. The effective surface 12 of the first mirror 11 can be configured [embodied] to be flat or concave. In this depicted embodiment, [case] the at least one effective surface 12 of the first

mirror 11 oriented along the length L01 of the illuminated strip 01 can restrict the light from at least one of the light sources 07 of the illumination arrangement 06 directed into the solid angle ω [omega] more closely to a second, smaller envelope surface AH2 than the at least one effective surface 12 of this first mirror 11, which is oriented along the width B01 of the illuminated strip 01, such as is shown in Fig. 6 in comparison with the beams in accordance with Fig. 5. Preferably at least one light source 07 of the illumination arrangement 06 has a first mirror 11 with at least two effective surfaces 12, which are symmetrical with [in] respect to the central beam 13 which is emitted by the light source 07.

[0050] A second mirror 16 can be provided, as depicted in Figs. 7 and 8 for use in [For] redirecting the radiation emitted by at least one of the light sources 07 of the illumination arrangement 06 in a central area 14 surrounding the central beam 13. At [, a second mirror 16 can be provided, as represented in Figs. 7 and 8, wherein its at] least one effective surface 17 of the second mirror 16 is arranged in the central area 14 surrounding the beam path of the central beam 13, within the solid angle ω [omega] of the light emitted by the light source 07. The [, wherein the] effective surface 17 of the second mirror 16 redirects the light emitted by at least one of the light sources 07 of the illumination arrangement 06 against at least one effective surface 12 of the first mirror 11, which at least one effective surface 12 is directed along the length L01 and/or the width B01 of the illuminated strip 01[, of the first mirror 11]. In this case, the light which is emitted by the light source 07 can preferably be more tightly focused along the length L01 of the illuminated strip 01 than along its width B01. The effective surface 17 of the second mirror 16 can also be embodied to be flat or concave. The light beams to be assigned to the central area 14, and

which are emitted by the respective light sources 07, are respectively indicated in Figs. 7 to 10 by solid arrow lines. The [, while the] light beams which are peripherally emitted in their respective solid angles ω [omega] by the light sources 07 are indicated by dashed arrow lines.

[0051] As depicted in [In accordance with] Figs. 9 and 10, it is alternatively also possible, in order to accomplish [for] the redirection of the light beams which are emitted by at least one of the light sources 07 of the illumination arrangement 06 in a central area 14 surrounding the central beam 13, to arrange at least one lens 18, and in particular a biconcave lens 18, in the central area 14 surrounding the central beam 13 and within the solid angle ω [omega] of the light which is emitted by at least one of the light sources 07 of the illumination arrangement 06. A [, wherein a] distance A18 exists between the light source 07 and a center Z18 of the lens 18. The [, wherein the] distance A18 is advantageously less than half the distance A07 between the light source 07 and the surface 02 of the material 03. In this case, the lens 18 can be embodied to be not rotationally symmetrical. This can be done [,] in order to preferably focus the light emitted by the light source 07 more tightly along the length L01 of the illuminated strip 01 than along its width B01.

[0052] Fig. 11 shows that the light sources 07 of the illumination arrangement 06 are preferably arranged in such a way that the respective solid angles ω [omega], or at least the envelope surfaces AH1, AH2 of the light which is emitted by at least two adjoining light sources 07 of the illumination arrangement 06, are overlaid on each other in at least a partial area 19 which illuminates the illuminated strip 01. This overlay is, in particular, also provided if the respective two [concerned] adjoining light sources 07 are arranged in two adjoining modules M61 to M65. It can also be seen in Fig. 11 that a respective first mirror 11, with at least one effective surface 12,

and preferably with two such effective surfaces 12, which are symmetrical in respect to each other, can be provided at each individual light source 07 of the illumination arrangement 06, at least along the width B01 of the illuminated strip 01.

[0053] The [Furthermore, the] illumination arrangement 06 can have a scattering body 38, or in other words, [i.e.] a light-scattering body, 38, such as for example, a lenticula or a prism foil, which may be located, as seen in Fig. 12 at a side of the illumination arrangement 06 facing the surface 02 of the material 03, i.e. at a light outlet side of the arrangement 06. The [, wherein the] scattering body 38 distributes the light which is radiated by the light sources 07 onto the surface 02 of the material 03 preferably exclusively, or at least quite preponderantly, along the length L01 of the illuminated strip 01. In a preferred embodiment of the present invention, the scattering body 38 and at least one of the mirrors 11, 16 of the illumination arrangement 06 are embodied as a single component, called a reflector module 39 as seen in Fig. 17. A [, wherein preferably a] group of, for example five or ten, light sources 07 are preferably arranged in a line next to each other and respectively radiate their light into a reflector module 39 [38] that is arranged along this row of light sources 07. For this purpose, the light sources 07 are arranged on the side of the reflector module 39 which is [38] located diametrically opposite the light outlet side or may even be recessed in that area [there] in a [the] reflector module 39. The reflector module 39 is a component which has been produced, for example, from a preferably transparent material by [means of] injection-molding techniques. Therefore, the reflector module 39 is configured [designed] as a particularly massive molded part, in which the scattering body 38 and at least one of the mirrors 11, 16 are together formed in such a way that no optically relevant border surface

separates the scattering body 38 from the at least one mirror 11, 16. Fig. 17 shows, in a perspective plan view, and by way of example, a reflector module 39 with a scattering body 38 which is [39,] preferably embodied integrated, at the light outlet side. The [, wherein the] scattering body 38 [39] at the light outlet side of the reflector module 39 is embodied, for example, as a fluted structure[, i.e. is for example] formed on the molded part. The [, wherein the] reflector module 39 is arranged in the illumination arrangement 06 in such a way that the parallel extending flutes of the fluted structure are preferably aligned with the movement direction 04 of the material 03. The mirrors 11, 16 and/or the lens 18 can be embodied to be integrated in the reflector module 39. Therefore, the reflector module 39 is preferably configured [designed] with a depression which is extending in the longitudinal direction of the illumination arrangement 06. The reflector module 39 is preferably constructed of several segments which are lined up with each other. Each [, wherein each] segment constitutes the light beam path fed into the reflector module 39 by one of the light sources 07. The reflector module 39 is preferably mounted on the board 21, which is supporting the light sources 07, or on the support 27, by, for example, [by means of] mounting elements 41 that are formed out of the reflector module 39. At least one reflector module 39 is preferably assigned to each one of the modules M61 to M65 which are arranged along the width B01 of the illuminated strip 01.

[0054] The [In this way the] scattering body 38 of the illumination arrangement 06, in a name which is the same as the arrangement of the mirrors 11, 16 and/or of the lens 18, simultaneously acts in a shaping and homogenizing manner, with respect [in regard] to the distribution of the light that is emitted by the light sources 07. The scattering body 38 contributes, in particular,

[contributes] to a shadow-free, diffused illumination of the illuminated strip 01, even on a surface 02 of the material 03 which may be provided with a delicate structure. Additionally, [wherein] in spite of the distance A07 each of the light sources 07 has from the surface 02 of the material 03, the illuminated strip 01 is simultaneously formed as a very bright illuminated band because of the illumination arrangement 06. The arrangement of the mirrors 11, 16 and/or of the lens 18, as well as the provision of the scattering bodies 38 in particular, contributes to the light exiting the illumination arrangement 06 with a homogeneous light distribution. The result is [, so] that [therefore] an inner structure of the illumination arrangement 06, such as, for example, [i.e.] the arrangement of its individual light sources 07, is not even represented on a reflecting surface 02 of the material 03, such as, for example, on a reflecting lacquer, a cold seal, a window thread, a patch, or the like. As [, and as] a result, this arrangement of individual light sources 07 does not become visible even when viewed under the respective reflection angle.

[0055] Fig. 12 represents a side elevation [plan] view of the optical system, in accordance with the present invention. The [wherein the] view takes place from a plane extending perpendicularly with [in] respect to the movement direction 04 of the material 03. The illumination arrangement 06 and the illuminated strip 01 which is illuminated by the illumination arrangement 06 on the surface 02 of the material 03 are arranged parallel, with [in] respect to each other, at a distance A07. However[, however], the extension of the illumination arrangement 06, i.e. its length B06, can, as seen in Fig. 12, be greater than the length L01 of the illuminated strip 01 or than the width B03 of the material 03. The illumination arrangement 06 is divided into several modules M61 to M65. In the [, i.e. in this] example of Fig. 12, the illumination arrangement 06 is divided into five

modules M61 to M65 which are arranged side-by-side in a line. The [, wherein the] light sources 07, which is arranged in every module M61 to M65, respectively, emit light toward the illuminated strip 01. The light that is reflected by the now illuminated strip 01 is then detected by the detector 09 of the detection device 08, which detector 09 is arranged at a distance A09 from the surface 02 of the material 03, and within a spatial detection angle α [alpha] which opens along the length L01 of the illuminated strip 01. The [, wherein in this example the] detection angle α [alpha] is, in this depicted embodiment of such dimensions that it registers the light which is reflected at the illuminated strip 01 over the entire length of the illuminated strip 01. The detection angle α [alpha] forms a cross-sectional area on the surface 02 of the material 03, so that the detection angle α [alpha] registers at least a part of the cross-sectional area of the light beam which is emitted by the illumination arrangement 06 and which is extending over the width B01 of the illuminated strip 01. The cross-sectional area which is registered by the detection angle α [alpha] preferably is at least as large as the area on the surface 02 of the material 03 that is defined by the length L 01 and by the width B01 of the illuminated strip 01. The illumination arrangement 06 and the detection device 08 are preferably arranged spaced apart from each other in the movement direction 04 of the material 03 in such a way that the light which is emitted by the light sources 07 of the illumination arrangement 06 onto the surface 02 of the material 03 is reflected by the surface 02 of the material 03 toward the detector 09 of the detection device 08 in accordance with the rule "the angle of incidence is equal to the angle of reflection". However, [But] the "angle of reflection" expected as a result of the "angle of incidence", or [i.e.] the reflection angle, can differ from the above mentioned ideal condition, which is based on a completely reflective [reflecting]

area. This variation can be [, as] a result of the nature of the surface 02 of the material 03, and in particular can be [as] a function of its structure, and in particular of its micro-structure.

[0056] The quality of an image that is taken by the detection device 08, by [means of] registering the light which is reflected at the illuminated strip 01, is substantially [decisively] dependent on the fact that the light sources 07 of the illumination arrangement 06 can emit light at a constant intensity. Fluctuations in the intensity of the light which is emitted by the light sources 07 have the same result in the detection device 08, with [in] regard to the signal provided to the image processing device 24, as would or do changes in the nature of the surface 02 of the illuminated material 03. The result is [, so] that the causes of a signal change cannot be detected in the image processing device 24. Under these circumstances, it is not possible to obtain dependable information regarding the nature of the surface 02 of the illuminated material 03 from an [am] image evaluation which is performed in the image processing device 24.

[0057] Measures which maintain the intensity of the light emitted by the light sources 07 of the illumination arrangement 06 offer relief from the potential problem of light intensity variations[in this case]. The light sources 07 used in the illumination arrangement 06 are preferably embodied as high- intensity light-emitting diodes 07 or as laser diodes 07, whose light intensity is a function of temperature. Steps that can be taken for stabilizing the temperature of the light sources 07, which are arranged on the support, in order to obtain a constant light intensity will be described subsequently [in what follows]. The advantage of the [proposed] solution in accordance with the present invention lies in that the thermal load on the light sources 07 is removed directly at the place where it occurs. Because [, because] of this thermal load removal, [which] it is possible to

obtain short recovery times.

[0058] The [Preferably the] light sources 07 are preferably arranged on a board 21, which can be equipped with additional electronic components and with strip conductors. The semi-conductor of the light-emitting diode 07 or of the laser diode 07 is preferably in direct contact with the board 21, which board 21 is configured [designed] as an MCPCB (metal core printed circuit board) or as a board 21 with a core of aluminum. Board 21 [, and] has, on its mounting side 32 which supports the light-emitting diodes 07 or the laser diodes 07, only a very thin cover on its heat- conducting base for forming [creating] the lowest possible heat transmission resistance.

[0059] Fig. 13 shows a board 21 with several light sources 07 arranged in lines thereon. The [, wherein the] board 21 itself is arranged on a support 27. Support [, wherein the support] 27 preferably has, in its interior, and preferably underneath the line-like or linear arrangement of the light sources 07, at least one conduit 28. A [, wherein a] liquid or a gaseous coolant, such as, for example, water or air, flows through this conduit 28. An inflow opening 29 is connected with the coolant inflow, and a[n] return flow opening 31 is connected with the return flow for use in feeding in and in removing the coolant. These openings are provided, preferably at the front or end face of the support. The [, wherein the] coolant flows through the support 27 , preferably in a straight line. Fig. 14 shows a support 27 through which the coolant flows in two opposite directions, because [by means] of which, a temperature profile is achieved in the support 27 which temperature profile is balanced along the line-shaped arrangement of the light sources 27. To accomplish [For] this purpose, the conduit 28 can be reversed by 180° at one end of the support 27 as seen in Fig. 14.

[0060] A regulating device, which is not specifically represented, can maintain the temperature of the coolant at the coolant inflow opening 29 and [of] the flow-through quantity of the coolant passing through the conduit 28 constant. Alternatively, the regulating device can also maintain [keep] a constant difference between the temperature of the coolant at the inflow and the temperature of the coolant at the outflow [constant]. In this case, the absolute temperature of the coolant is of secondary [less] importance. More importantly, [instead] a maximally permissible temperature for the light sources 07, which results from the heat transfer resistance of the involved materials, should not be exceeded. This [, which] is prevented by the regulating device, by [means of] monitoring the temperature of the light sources 07, or of the coolant and by reacting with corrective steps. If no coolant, whose temperature or flow-through quantity can be regulated, is available, cooling of the light sources 07 can also take place by the use [means] of an external cooling device, which is [(not specifically represented)], and which is not connected with the board 21.

[0061] Fig. 15 shows an alternative to the use of a flowing coolant. The board 21, which is equipped with the light sources 07, is again arranged on a support 27. The [, wherein the] support 27 itself is arranged on at least one Peltier element 33, and is preferably arranged on several such Peltier elements 33. The [, wherein the] Peltier elements 33 are each connected with a cooling body 34 which is thermally separated from the support 27. A required temperature measurement, for use in regulating the at least one Peltier element 33, by [means of] an electronic regulating device, which is not specifically represented, is taken directly on the support 27 by a temperature sensor 36. In the [Then, in] case of a fluctuating ambient temperature, only the temperature of the

cooling body 34 fluctuates. The [, but not the] temperature of the light sources 07 arranged on the board 21 does not fluctuate . The electronic regulating device can be integrated into the control device 23 which is connected with the illuminating arrangement 06.

[0062] Since the movement of the moving material 03 in a printing press, or in a machine which further processes a printed product, takes place at a speed of several meters per second, and, for example, at a speed of 3 m/s or more, and wherein in a sheet printing press, for example, 15,000 sheets 03 or more [per hour] are imprinted per hour and are transported through the printing press, the optical system must be laid out in such a way that a usable image of the moving material 03 can be taken. Consideration must be given to the fact that, with a detection device 08 configured [designed] as a line-scanning camera 08, the detected amount of the light, which is reflected by the surface 02 of the moving material 03, changes as a function of the speed of the moving material 03. The brightness of the taken picture also changes as a function of the speed of the moving material 03 [with this]. It is possible that the taken picture may be [becomes] useless, in the case of greater speed changes, such as can customarily occur in the above- mentioned presses.

[0063] Instead of synchronizing the picture-taking of the detection device 08, such as, for example, the line-scanning camera 08, with the speed of the moving material 03 by the use [means] of an encoder, it is proposed to synchronize a length of switched-on time t3 of a single light source 07 or of a group of light sources 07 of the illumination arrangement 06, which light source 07 or group of light sources 07 are preferably triggered by an electrical current source 22, and in particular by a constant electrical current source 22, which is controlled by the control device 23, with the triggering, or with [i.e.] the length of exposure time t1 of the line-scanning

camera 08. The result is [, so] that the surface 02 of the moving material 03 is always illuminated with the same amount of light, independently of the speed of the moving material 03. From this a constant brightness of [results for] the picture taken by the detection device 08, such as, for example, by the line-scanning camera 08 results, over a wide range of the speed of the moving material 03. The [, because the] control device 23 always sets the length of the switched-on time t_3 of a single light source 07 or of a group of light sources 07 of the illumination device 06 lower than the length of exposure time t_1 of the line-scanning camera 08.

[0064] As previously [already] described, several groups of light sources 07 are preferably provided in the illumination arrangement 06. Each [, to each] of the several groups of light sources 07 [which] preferably has at least one electrical current source 22, and in particular has a constant electrical current source 22[, is] assigned to it. The lengths of switched-on times t_3 of the light sources 07 are controlled by the control device 23, which is connected with the illumination arrangement 06, for example in groups. These lengths t_3 can[, or] also be controlled singly independently of each other by the respective electrical current sources 22. A [, so that a] profile of the amount of light can be set over the length of the light sources 07 of the illumination arrangement 06, which are preferably arranged in lines. Setting a profile of the amount of light, preferably along the length L_{01} of the illuminated strip 01, has the advantage that transmission losses can be compensated for by the use [means] of an optical device, which is not specifically represented, of the detection device 08, for example the line- scanning camera 08.

[0065] It can moreover be provided that a light sensor 37, which is connected with the control device 23, as seen in Fig. 2, measures the amount of light that is radiated by the light sources 07 of

the illumination arrangement 06. This can be done in order to match the length of the switched-on time t3 of the light sources 07, which are controlled by the control device 23, on the basis of the measuring signal of the light sensor 37, for example, to a degradation behavior of the light sources 07. By [, and by means of] controlling the light sources 07, it is possible to compensate for a reduced output of the amount of light radiated because of aging of the light sources 07. Also, the control device 23 can match, and in particular can automatically match, the length of the switched-on time t3 of the light sources 07 with [to] different optical properties of the material 03 to be illuminated, for example.

[0066] Fig. 16 shows the chronological behavior of the detection device 08, such as, for example, the line-scanning camera 08, and also shows the chronological behavior [that] of the light sources 07 of the illumination arrangement 06. The line-scanning camera 08 is switched on at a defined point in time in accordance with the upper, first time progression of Fig. 16. The [, so that the] length of exposure time t1 of the line-scanning camera 08 starts at this point in time. Following the end of the exposure time t1, an off time t2, which is a function of the speed of the moving material 03, immediately follows between two adjoining image lines of the line-scanning camera 08 which follow each other in the movement direction 04 of the material 03. In accordance with the center, second time progression depicted in Fig. 16, at least one light source 07, which is triggered as a function of the control of the line-scanning camera 08, is turned on by the electrical current source 22, which controlled by the control device 23 simultaneously with the length of exposure time t1 of the line-scanning camera 08. Following [wherein, following] a delay time t4 for switching on the light source 07, or in other words, [i.e.] after a physically required time until

the start of light emission, this light source 07 then remains switched on for a length of switched-on time t3. The [, wherein the] length of switched-on time t3, and preferably also a sum of the times consisting of a delay time t4 and of the length of switched-on time t3, is of shorter length than is the length of exposure time t1 of the line-scanning camera 08. The chronological behavior of the line-scanning camera 08 and of the light sources 07 is periodically repeated in accordance with [according to] the above-[previously] described correlation. The chronological behavior of the switched-on time t5 for a constant light source is represented in the lower, third time progression in Fig. 16 only as a comparison with the chronological behavior of the triggered switched-on time t3 of the light source 05.

[0067] While a preferred embodiment of an optical system for forming an illuminated pattern, in accordance with the present invention, has been set forth fully and completely herein above, it will be apparent to one of skill in the art that various changes, for example in the type of images being processed, in the apparatus used for moving the material in a movement direction and the like could be made without departing from the true spirit and scope of the present invention which is accordingly to be limited only by the appended claims.

What is claimed is:

[List of Reference Symbols]

- 01 Pattern, illuminated strip
- 02 Surface
- 03 Material, sheet, web of material, imprinted
material, securities, banknote
- 04 Movement direction
- 05 -
- 06 Illumination arrangement
- 07 Light source, light-emitting diode, laser diode
- 08 Detection device, camera, line-scanning camera,
line-scanning color camera
- 09 Detector, CCD array, photodiode
- 10 -
- 11 Mirror, first
- 12 Effective surface
- 13 Central beam
- 14 Central area
- 15 -
- 16 Mirror, second
- 17 Effective surface
- 18 Lens
- 19 Partial area
- 20 -
- 21 Board
- 22 Electrical current source, constant electrical
current source
- 23 Control device
- 24 Image processing device
- 25 -
- 26 Partition
- 27 Support
- 28 Conduit
- 29 Opening
- 30 -
- 31 Opening
- 32 Mounting side
- 33 Peltier element
- 34 Cooling body
- 35 -
- 36 Temperature sensor]

[37 Light sensor
38 Scattering body
39 Reflector module
40 -
41 Mounting element

A07 Distance
A09 Distance
A18 Distance
B01 Width
B03 Width
B06 Length
L01 Length
Z18 Center

AH1 Envelope surface, first
AH2 Envelope surface, second
AK Surface, spherical surface
M61 Module
M62 Module
M63 Module
M64 Module
M65 Module

t1 Length of exposure time
t2 Off time
t3 Length of switched-on time
t4 Delay time
t5 Length of switched-on time

alpha Detection angle
omega Solid angle]